


# 304 HSS DOUBLE-END DRILL BIT, GROUND, SPLIT POINT



## DRIVE



D Ø mm	L2 mm	L1 mm		EAN 4016707...	
3,00	10	46	10	100017	304 000 300
3,10	10	46	10	100024	304 000 310
3,20	10	49	10	100031	304 000 320
3,30	10	49	10	100048	304 000 330
3,50	13	52	10	100062	304 000 350
4,00	13	55	10	100086	304 000 400
4,10	13	55	10	100093	304 000 410
4,20	13	55	10	100109	304 000 420
4,50	16	58	10	100123	304 000 450
4,80	16	58	10	100130	304 000 480
5,00	16	62	10	100147	304 000 500
5,10	16	62	10	100154	304 000 510
5,20	16	62	10	100161	304 000 520

## EXECUTION

- Double-ended, right-hand cutting, type N, works standard
- High-performance high-speed steel
- 118° conical section
- Diametral tolerance h8
- Profile-ground
- Cross-ground finish to DIN 1412 C

## FOR USE IN



- For drilling thin sheets for car bodies and metal fabrication, for rivet holes, screw holes etc., in steel, zinc, brass, aluminium, copper sheet and plastic panels

## APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use

## PACKAGING

