




**Type:** MMS-MS flange head

**Material:** steel, hardened

**Surface:** bright zinc plated

Color code  
HECO-Label

**Recess:** T-Drive



Size D x L [mm]	Article No.	Drill diameter $d_0$ [mm]	Clamping strength $t_{fix}$ [mm]	Head diameter [mm]	Recess	Ap- proval	Packing unit [pcs.]	Pieces per outer carton [pcs.]	Pieces per pallet [pcs.]	Gross price [€/100 pcs.]
--------------------	-------------	---------------------------------	--	--------------------------	--------	---------------	---------------------------	--------------------------------------	--------------------------------	-----------------------------

#### VARIANTA - BOXES FOR PROFESSIONALS

<b>7,5</b>	45	21000	6,0	1	17,0	T-30	O	100	1.000	48.000	29,25
	50	36765	6,0	5	17,0	T-30	O	100	1.000	48.000	33,35
	60	42616	6,0	5	14,5	T-30	•	50	500	24.000	38,30
	60	36767	6,0	5	17,0	T-30	O	50	500	24.000	38,30

• = according to ETA 05/0010

O = according to the German DIBt-approval no. Z-21.1-1503

**Type:** MMS-S hexagon head


**Material:** stainless steel A4 1.4401



**Surface:** self-colour

Color code  
HECO-Label

**Recess:** hexagon head



Size D x L [mm]	Article No.	Drill diameter d <sub>0</sub> [mm]	Clamping strength t <sub>fix</sub> [mm]	Head diameter [mm]	Recess	Ap- proval	Packing unit [pcs.]	Pieces per outer carton [pcs.]	Pieces per pallet [pcs.]	Gross price [€/100 pcs.]
--------------------	-------------	--	---	--------------------------	--------	---------------	---------------------------	--------------------------------------	--------------------------------	-----------------------------

VARIANTA - BOXES FOR PROFESSIONALS

<b>7,5</b>	50	23098*	6,0	10	13,0	SW-13	•	50	500	24.000	310,15
	75	42989	6,0	10	13,0	SW-13	•	50	500	24.000	315,15
<b>10,0</b>	85	41202	8,0	10	16,0	SW-16	•	25	250	12.000	414,60
	95	41205	8,0	20	16,0	SW-16	•	25	250	12.000	431,15
<b>12,0</b>	100	41208	10,0	10	18,0	SW-18	•	25	250	12.000	655,05
	120	41211	10,0	30	18,0	SW-18	•	25	100	9.600	688,25

• = according to ETA 05/0011

\*Not qualified for fastenings in case of fire