



# WINSTA® MIDI special Sockets and Plugs, 5-Pole

<p>2 x 0.5 – 4 mm<sup>2</sup> ①   2 x AWG 20 – 12</p> <p>400 V/6 kV/3 I<sub>N</sub> 25 A ③</p> <p> 9 mm / 0.35 in</p> <p>② Approvals</p>	<p>2 x 0.5 – 4 mm<sup>2</sup> ①   2 x AWG 20 – 12</p> <p>400 V/6 kV/3 I<sub>N</sub> 25 A ③</p> <p> 9 mm / 0.35 in</p> <p>② Approvals</p>
---	---



Description	Color	Item No.	Pack. Unit	Color	Item No.	Pack. Unit
Pluggable connectors, 4-pole, with CAGE CLAMP®S connection	Socket without strain relief housing			Plug without strain relief housing		
	● gray	770-245	50	● gray	770-255	50
	● gray	770-245/060-000*	50	● gray	770-255/060-000*	50
	● gray	770-245/062-000*	50	● gray	770-255/062-000*	50
	● gray	770-245/064-000*	50	● gray	770-255/064-000*	50
	● light green	770-265	50	● light green	770-275	50
	● light green	770-265/073-000*	50	● light green	770-275/073-000*	50
	● pink	770-285	50	● pink	770-295	50
	● pink	770-285/080-000*	50	● pink	770-295/080-000*	50
	● pink	770-285/082-000*	50	● pink	770-295/082-000*	50
	* Pole marking, see page 227.			* Pole marking, see page 227.		

Item-Specific Accessories						
			<p><b>Strain relief housing, for 2 cables,</b></p> <p>5 – 9 mm diameter</p> <p>● black 770-505/023-000 25</p> <p>● white 770-515/023-000 25</p>			
			<p><b>Strain relief housing, for 2 cables,</b></p> <p>9 – 13 mm diameter</p> <p>● black 770-505 25</p> <p>● white 770-515 25</p>			

Accessories, 770 Series						
			<p><b>Locking lever, for "flying leads,"</b></p> <p>manually operated</p> <p>● black 770-101 100 (4x25)</p> <p>● white 770-121 100 (4x25)</p>			
			<p><b>Locking lever, for "flying leads,"</b></p> <p>tool operated</p> <p>● black 770-111 100 (4x25)</p> <p>● white 770-131 100 (4x25)</p>			

Info	Dimensions
------	------------

- ① Conductor sizes: 0.5 – 4 mm<sup>2</sup> "s + f-st"  
0.5 – 2.5 mm<sup>2</sup> "stranded"
  - ② For "International Certification Organizations" and "Approvals - User Guide," see pages 240 to 243.
  - ③ Full rated current can only be applied to a maximum of 3 poles!
- Standard printing (without suffix number)
- gray Coding B (1 2 3 4 5)
  - light green Coding B (1 2 3 4 5)
  - pink Coding B (1 2 3 4 5)
- For additional pole marking, see page 227.
- For coding information, see pages 224 to 226.  
Fire load data available upon request.

